

## Medium size Socket for Power IC Single in Line


2.54mm/0.10" pitch

### Specifications

Dielectric Strength: AC300Vrms 1min  
Insulation Resistance: 1000MΩmin  
Operating Temperature: -45°C~+150°C

### Material

Sleeve : Brass, Gold flash over Ni  
Contact : Beryllium, Gold plating over Ni  
Insulator: PPS or LCP Black




### How to order

**PDSA-□□□-S □□ GG**

Code  
See below

Number of Positions  
2~16



Code	Parts Number	(Socket Pin P/N)	Contact depth (d)	Technical Data /page
1076	<a href="#">PDSA-1076-S□□-GG</a>	(PD1581076-L158-GG)	2.9	Fig. 1/8H3
876	<a href="#">PDSA-876-S□□-GG</a>	(PD158876-L158-GG)	2.2	Fig. 2/8H3
CM1	<a href="#">PDSA-CM1-S□□-GG</a>	(PD20CM1-L158-GG)	3.4	Fig. 3/8H3
CM2	<a href="#">PDSA-CM2-S□□-GG</a>	(PD20CM2-L158-GG)	3.3	Fig. 4/8H4
1081	<a href="#">PDSA-1081-S□□-GG</a>	(PD201081-L158-GG)	3.8	Fig. 5/8H4

